









- ⇔Housing in Signal Orange for simple differentiation from standard tools
- ⇔Insulated and VDE certified to 1000 V for increased safety when working on potentially voltage-carrying parts
- ←For cutting Al/St conductors (ACSR) to DIN EN 50182, solid Al/Cu cables to DIN EN 60228, Class 1 and laminated copper bus bars
- ⇐Extremely robust design and lightweight
- ⇔Slim cutting head ideal when space is critical
- ←All tool data in view thanks to the built-in display

Characteristics

- Choose your battery system: Bosch or Makita
- Open head, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete
- Manual retract stop (MRS) for efficient operations
- Always ready-to-use thanks to battery charge and service display
- All data can be easily read out via Bluetooth

Suitable for

Al/St wire (ACSR)

Technical data			
Head type	cutter open		
Cutting range	max. 18 mm dia. (depending on cable/wire type)		
Cutting force	23 kN		
Cutting cycle	2 s to 4 s (depending on cable size)		
Charging time	15 min.		
Weight incl. battery	2.1 kg		
Ambient temperature	-10° to +40 °C		
Item		Part NoBosch	Part NoMakita
VDE battery powered hydraulic cutting tool 20mm dia.		n dia. ES20ISB	ES20ISM
Scope of supply			
Bosch battery 18 V / 2.0 Ah, Li-Ion		RALB1EU	
Bosch quick-charger for 18 V Li-lon battery		LGLB1EU	
Makita battery 18 V / 1.5 Ah, Li-Ion			RAL1
Makita quick-charger for 18 V Li-lon battery			LGL1
Plastic case		KK50IS	KK50IS
Accessories			
Bosch Akku 18 V / 5,0 Ah, Li-lon		RALB2EU	
Makita battery 18 V / 3.0 Ah, Li-lon (54 Wh)			RAL2
Replacement blade		ES20E	ES20E
Makita battery 18 V / 3.0 Ah, Li-lon (54 Wh)			